



9501

Multi-Conductor - Computer Cable for EIA RS-232 Applications



Description

24 AWG stranded (7x32) TC conductors, semi-rigid PVC insulation, twisted pairs, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain Wire, PVC jacket.

Put Ups and Colours

Item #	Putup	Ship Weight	Jacket Colour	Notes	Item Description
9501 060100	100 FT	2.000 LB	CHROME	C	2 #24 PVC FS PVC CHR
9501 0601000	1,000 FT	14.000 LB	CHROME		2 #24 PVC FS PVC CHR
9501 060500	500 FT	7.000 LB	CHROME		2 #24 PVC FS PVC CHR
9501 060U1000	1,000 FT	14.000 LB	CHROME		2 #24 PVC FS PVC CHR
9501 060U500	500 FT	7.500 LB	CHROME		2 #24 PVC FS PVC CHR

Notes:

C = Create Reel Put-up

Application

NEC (UL) Specification	CMG
CEC/C (UL) Specification	CMG
AWM Specification	UL Style 2464 (300 V 80°C)
CSA Specification	AWM I A
EU CE Mark	
EU RoHS Compliant (commence date: dd/mm/yyyy)	(01/04/2005)

Flame Test

UL Flame Test FT4

Plenum/Non-Plenum

Plenum	88641, 82641
Plenum Number	