



YY Cable PVC/PUR UL/CSA/CE



Technical Information:

Temperature Limits: - 5°C to 80°C Flexing & -40°C to +80°C Static

Bending Radius: Fixed 4 x Overall Diameter / Flexing: 7.5 x Overall Diameter

Core Identification:

JZ – Number Coded – 2 core – Black cores with white

3 core - Black cores with white number plus Green/Yellow

Voltage Rating : According to UL & CSA 600V

Cable construction : PVC core insulation & PUR jacket to Ral 7001

Part No	Conductor	Stranding AWG	Cores	Weight (KG/KM)	O.D (mm)
CC/2X0.5YYULP	0.5	20	2	52	5.8
CC/3X0.5YYULP	0.5	20	3	64	6.2
CC/4X0.5YYULP	0.5	20	4	72	6.6
CC/5X0.5YYULP	0.5	20	5	88	7.2
CC/7X0.5YYULP	0.5	20	7	130	8.5
CC/12X0.5YYULP	0.5	20	12	196	10.8
CC/18X0.5YYULP	0.5	20	18	260	12.8
CC/25X0.5YYULP	0.5	20	25	368	15.5
CC/34X0.5YYULP	0.5	20	34	502	17.6
CC/42X0.5YYULP	0.5	20	41	594	19.7
CC/2X1YYULP	1.0	18	2	57	6.2
CC/3X1YYULP	1.0	18	3	68	6.6
CC/4X1YYULP	1.0	18	4	79	7.2
CC/5X1YYULP	1.0	18	5	97	7.8
CC/7X1YYULP	1.0	18	7	141	9.1
CC/12X1YYULP	1.0	18	12	211	11.7
CC/18X1YYULP	1.0	18	18	284	14.0
CC/25X1YYULP	1.0	18	25	394	17.0
CC/34X1YYULP	1.0	18	34	521	19.2
CC/42X1YYULP	1.0	18	41	609	21.0



YY Cable PVC/PUR UL/CSA/CE

Part No	Conductor	Stranding AWG	Cores	Weight (KG/KM)	O.D (mm)
CC/2X1.5YYULP	1.5	16	2	75	6.9
CC/3X1.5YYULP	1.5	16	3	96	7.5
CC/4X1.5YYULP	1.5	16	4	117	8.1
CC/5X1.5YYULP	1.5	16	5	140	8.7
CC/7X1.5YYULP	1.5	16	7	186	10.6
CC/12X1.5YYULP	1.5	16	12	319	13.4
CC/18X1.5YYULP	1.5	16	18	451	15.8
CC/25X1.5YYULP	1.5	16	25	625	18.9
CC/34X1.5YYULP	1.5	16	34	850	22.0
CC/50X1.5YYULP	1.5	16	41	1041	23.7
CC/2X2.5YYULP	2.5	14	2	115	8.2
CC/3X2.5YYULP	2.5	14	3	143	8.7
CC/4X2.5YYULP	2.5	14	4	185	10.1
CC/5X2.5YYULP	2.5	14	5	221	10.9
CC/7X2.5YYULP	2.5	14	7	293	13.1
CC/12X2.5YYULP	2.5	14	12	563	16.7
CC/18X2.5YYULP	2.5	14	18	854	19.6
CC/25X2.5YYULP	2.5	14	25	1188	24.0
CC/3X4YYULP	4	12	3	232	11.2
CC/4X4YYULP	4	12	4	298	12.5
CC/5X4YYULP	4	12	5	358	13.8
CC/7X4YYULP	4	12	7	460	16.3
CC/3X6YYULP	6	10	3	360	12.9
CC/4X6YYULP	6	10	4	402	14.2
CC/5X6YYULP	6	10	5	484	15.9
CC/7X6YYULP	6	10	7	630	19.4
CC/3X10YYULP	10	8	3	535	16.9
CC/4X10YYULP	10	8	4	653	18.5
CC/5X10YYULP	10	8	5	786	20.3
CC/7X10YYULP	10	8	7	1100	22.3
CC/3X16YYULP	16	6	3	810	20.5
CC/4X16YYULP	16	6	4	1045	23.2
CC/5X16YYULP	16	6	5	1260	25.7
CC/3X25YYULP	25	4	3	1180	25.0
CC/4X25YYULP	25	4	4	1507	28.1
CC/5X25YYULP	25	4	5	1858	30.9