



## YY Cable TPE/PUR Ce Approved



### Technical Information:

**Temperature Limits:** - -40°C to 90°C Flexing & -50°C to +90°C Static

**Bending Radius:** Static 4 x Overall Diameter Flexing: 15 x Overall Diameter

### Core Identification:

**JZ – Number Coded – 2 core – Black cores with white**

3 core - Black cores with white number plus Green/Yellow

**Voltage Rating :** 300/500 V

**Cable construction :** TPE core insulation & PUR jacket to Ral 7001

Part No	Conductor	Stranding	Cores	Weight	O.D (mm)
CC/2X0.5YYTPE	0.5	16/0.20	2	39	5.9
CC/3X0.5YYTPE	0.5	16/0.20	3	46	6.2
CC/4X0.5YYTPE	0.5	16/0.20	4	56	6.9
CC/5X0.5YYTPE	0.5	16/0.20	5	65	7.4
CC/7X0.5YYTPE	0.5	16/0.20	7	92	9.1
CC/12X0.5YYTPE	0.5	16/0.20	12	149	11.5
CC/18X0.5YYTPE	0.5	16/0.20	18	207	13.2
CC/25X0.5YYTPE	0.5	16/0.20	25	274	15.0
CC/34X0.5YYTPE	0.5	16/0.20	34	392	18.7
CC/42X0.5YYTPE	0.5	16/0.20	41	458	20.0
CC/2X0.75YYTPE	0.75	24/0.20	2	48	6.4
CC/3X0.75YYTPE	0.75	24/0.20	3	58	6.8
CC/4X0.75YYTPE	0.75	24/0.20	4	67	7.4
CC/5X0.75YYTPE	0.75	24/0.20	5	88	8.6
CC/7X0.75YYTPE	0.75	24/0.20	7	119	10.0
CC/12X0.75YYTPE	0.75	24/0.20	12	193	12.4
CC/18X0.75YYTPE	0.75	24/0.20	18	269	14.4
CC/25X0.75YYTPE	0.75	24/0.20	25	378	17.2
CC/34X0.75YYTPE	0.75	24/0.20	34	508	20.4
CC/42X0.75YYTPE	0.75	24.0.20	41	598	22.0



## YY Cable TPE/PUR Ce Approved

Part No	Conductor	Stranding	Cores	Weight (KG/KM)	O.D (mm)
CC/2X1YYTPE	1	32/0.20	2	57	6.8
CC/3X1YYTPE	1	32/0.20	3	69	7.2
CC/4X1YYTPE	1	32/0.20	4	90	8.2
CC/5X1YYTPE	1	32/0.20	5	100	8.9
CC/7X1YYTPE	1	32/0.20	7	182	10.5
CC/12X1YYTPE	1	32/0.20	12	230	13.0
CC/18X1YYTPE	1	32/0.20	18	325	15.1
CC/25X1YYTPE	1	32/0.20	25	476	18.7
CC/34X1YYTPE	1	32/0.20	34	616	21.6
CC/41X1YYTPE	1	32/0.20	41	724	23.2
CC/2X1.5YYTPE	1.5	30/0.25	2	92	8.3
CC/3X1.5YYTPE	1.5	30/0.25	3	108	8.8
CC/4X1.5YYTPE	1.5	30/0.25	4	144	9.9
CC/5X1.5YYTPE	1.5	30/0.25	5	168	10.8
CC/7X1.5YYTPE	1.5	30/0.25	7	230	12.9
CC/12X1.5YYTPE	1.5	30/0.25	12	306	14.7
CC/18X1.5YYTPE	1.5	30/0.25	18	464	17.9
CC/25X1.5YYTPE	1.5	30/0.25	25	641	20.8
CC/34X1.5YYTPE	1.5	30/0.25	34	857	24.9
CC/41X1.5YYTPE	1.5	30/0.25	41	1010	26.7
CC/2X2.5YYTPE	2.5	50/0.25	2	120	10.0
CC/3X2.5YYTPE	2.5	50/0.25	3	148	10.5
CC/4X2.5YYTPE	2.5	50/0.25	4	184	11.8
CC/5X2.5YYTPE	2.5	50/0.25	5	224	13.0
CC/7X2.5YYTPE	2.5	50/0.25	7	301	14.7
CC/12X2.5YYTPE	2.5	50/0.25	12	489	18.0
CC/3X4YYTPE	4	56/0.30	3	240	12.3
CC/4X4YYTPE	4	56/0.30	4	297	13.7
CC/5X4YYTPE	4	56/0.30	5	360	15.2
CC/7X4YYTPE	4	56/0.30	7	540	20.8
CC/3X6YYTPE	6	84/0.30	3	370	14.2
CC/4X6YYTPE	6	84/0.30	4	472	15.8
CC/5X6YYTPE	6	84/0.30	5	581	17.5
CC/7X6YYTPE	6	84/0.30	7	698	22.0
CC/3X10YYTPE	10	80/0.40	3	560	18.6
CC/4X10YYTPE	10	80/0.40	4	718	20.5
CC/5X10YYTPE	10	80/0.40	5	896	22.7
CC/7X10YYTPE	10	80/0.40	7	1295	20.9
CC/3X16YYTPE	16	126/0.40	3	940	23.5
CC/4X16YYTPE	16	126/0.40	4	1068	25.7
CC/5X16YYTPE	16	126/0.40	5	1810	28.5