




ENCODER PUR



TECHNICAL DATA

	Minimum bending radius	90 mm
	Maximum speed	240 m/min
	Maximum acceleration	20 m/s ²
	Conductor	Flexible cond. complying with: NFC 32012 Class 5/6, CEI 20-29 Class 5/6, IEC 228 Class 5/6, VDE 0295 Class 5/6
	Insulation	Polyolefin
	Colour code	Sec. 0,25 mm ² : Br/Gn-Gry/Pk-Bl/Vi-Rd/Blk Sec. 0,5/1 mm ² : Wht-Br
	Taping	Soft tape
	Shield	Tinned copper braid covering 85%
	Taping	Soft tape
	Jacket	Polyurethane Colour: orange Ral 2003
	Service temperature	Rating: -30 +80 °C Storage: -40 +85 °C
	Voltage	300 V
	Dielectric strength	1500 V
	Insulation resistance	>250 Mohm. Km

NORMATIVE REFERENCE

Oil resistance
VDE 0472 part 803 A/B (04/1986)
UL 1581 - VDE 0282 Teil 10
HD 22.10 S1

Max pulling strength
20 N/mm²

UL-CSA approval
AWM 80 °C - 300V
CSA AWM 75 °C - 300V FT1

Toxicity
Halogen free

FORMATION	CODE	DIAM. NOM. mm	CU kg/km
(4x2x0.25+2x1) SK	13MYI 17Z 10P	8.8	74
(4x2x0.25+2x0,50) SK	13MYI 21Z 10P	8.5	70