













TACHYMETER CEI 20-22/II




Contact Cables
The Cable Specialists





TECHNICAL DATA


	Minimum bending radius	90 mm
	Maximum speed	60 m/min
	Maximum acceleration	2 m/s ²
	Conductor	Flexible cond. complying with: NFC 32012 Class 5, CEI 20-29 Class 5, IEC 228 Class 5, VDE 0295 Class 5
	Insulation	PVC complying with: NFC-CEI-VDE-IEC
	Colour code	Wht-Br-Gn-Ye-Gry-Wht/Br Or-Bl-Rd-Blk-Vi-Wht/Blk
	Shield	Total tinned copper braid covering 85%
	Jacket	Special compound type OFS Colour: green RAL 6018
	Service temperature	Rating: -10 +80 °C Storage: -40 +80 °C
	Voltage	30 V
	Dielectric strength	1500 V
	Insulation resistance	>100 Mohm. Km

NORMATIVE REFERENCE

 Oil resistance
VDE 0472 part 803/B (04/1986)
EN 60811.2.1
VDE 0282 p. 10
HD 22.10 S1

 Refrigerant oil resistance
CNOMO E. 03.40.150
NFT 46-013

 Flame resistance
CEI EN 50265-2-1, DIN EN 50265-2-1,
NFC 32070 C2, IEC 60332.1.1

 Fire resistance
CEI 20-22/II, DIN EN 50266-2-5
NFC 32070 cat. C1 Test 2,
IEC 60332.3.24 cat. C

FORMATION	CODE	DIAM. NOM. mm	CU kg/km
(12x0.23) SK	13-MYS24X12R	7.5	49