



TACHYMETER PUR

Contact Cables The Cable Specialists

TECHNICAL DATA

	Minimum bending radius	70 mm
	Maximum speed	240 m/min
	Maximum acceleration	20 m/s ²
	Conductor	Flexible cond. complying with: NFC 32012 Class 6, CEI 20-29 Class 6, IEC 228 Class 6, VDE 0295 Class 6
	Insulation	PP
	Colour code	Wht-Br-Gn-Ye-Gry-Wht/Br Or-Bl-Rd-Blk-Vi-Wht/Blk
	Taping	Soft tape
	Shield	Total tinned copper braid covering 85%
	Taping	Soft tape
	Jacket	Polyurethane complying with: VDE 0250-818 Colour: green RAL 6018
	Service temperature	Rating: -30 +80 °C Storage: -40 +80 °C
	Voltage	30 V
	Dielectric strength	1500 V
	Insulation resistance	>10 Mohm. Km

NORMATIVE REFERENCE

Oil resistance
VDE 0472 part 803 A/B (04/1986)
UL 1581 - VDE 0282 Teil 10
HD 22.10 S1

Flame resistance
CEI EN 50265-2-1, DIN EN 50265-2-1,
NFC 32070 C2, IEC 60332.1.1

Toxicity
Non alogeno Halogen fre

UL-CSA approval
AWM 80 °C - 30V
© AWM 75 °C - 30V FT1

FORMATION	CODE	DIAM. NOM. mm	CU kg/km
(12x0.23) SK	13MYS 24X 12P-V1	6.90	48