



# TACHYMETER PUR



## TECHNICAL DATA

	Minimum bending radius	90 mm
	Maximum speed	240 m/min
	Maximum acceleration	20 m/s <sup>2</sup>
	Conductor	Flexible cond. complying with: NFC 32012 Class 6, CEI 20-29 Class 6, IEC 228 Class 6, VDE 0295 Class 6
	Insulation	Polyolefin
	Colour code	Grn-Br-Gry-Ye-Blk-BI-Rd-Wht-Pk
	Taping	Soft tape
	Shield	Tinned copper braid covering. 85%
	Taping	Soft tape
	Jacket	Polyurethane Colour: orange Ral 2003
	Service temperature	Rating: -30 +80 °C Storage: -40 +80 °C
	Voltage	300 V
	Dielectric strength	1500 V
	Insulation resistance	>250 Mohm. Km

Indramat® it is a Rexroth Indramat GmbH trademark

### NORMATIVE REFERENCE

Oil resistance  
VDE 0472 part 803 A/B (04/1986)  
UL 1581 - VDE 0282 Teil 10  
HD 22.10 S1

Max pulling strength  
20 N/mm<sup>2</sup>

UL-CSA approval  
AWM 80 °C - 300V  
AWM 75 °C - 300V FT1

Toxicity  
Halogen free

FORMATION	CODE	DIAM. NOM. mm	CU kg/km
<b>(9x0.50) SK</b>	13MYI 21X 09P	8.8	75